

October 23rd, 2018

Cathy Pasion

Campus and Community Planning
University of British Columbia
2210 West Mall
Vancouver BC, V6T 1Z4

Re: Stadium Road Neighbourhood i-Tree Hydro Assessment

Diamond Head Consulting Ltd. (DHC) was asked by UBC Campus + Community Planning to assess the stormwater runoff in the proposed Stadium Road neighbourhood considering different development scenarios. In a first memo, DHC estimated the stormwater management contribution of the Ropes Course to the neighbourhood and estimated current stormwater runoff conditions that will serve as a baseline to evaluate future development scenarios. The purpose of this second memo is to summarize the work done on the following items:

- Evaluating changes to stormwater runoff with changes in future development options 1 and 2 in a business as usual condition where no green infrastructure is integrated
- Evaluating the feasibility of reaching a net zero increase in runoff in Option 1 with the use of individual green infrastructure including rain gardens, cisterns and green roofs

The next step in this project will involve developing a scenario that mixes the preferred types of green infrastructure to create a realistic development scenario that achieves UBC's net zero target: no increase in runoff into storm drains as compared to current conditions.

The results reported in this memo refer to three different types of runoff.

1. **Impervious runoff** refers to stormwater runoff generated on impervious surfaces; it is assumed to be the volume of runoff managed by UBC's stormwater infrastructure.
2. **Pervious runoff** refers to runoff generated on saturated soil.
3. **Surface runoff** refers to the combination of both types of runoff.

Business as usual future development scenarios:

DHC developed surface cover estimates for two development options provided by UBC: Option 1 and Option 2. These business as usual scenarios assumed that no green infrastructure would be included outside of the green space included in the neighbourhood plans. Maps for the current condition and business as usual for Option 1 and 2 are provided in Appendix 1, with detailed surface cover percentages in Appendix 2.

In the current condition’s scenario, all streets, sidewalks, buildings and the sports field were assumed to be directly connected to the stormwater drainage infrastructure, while the compacted gravel area was assumed to be impervious but not directly connected. Given these assumptions, the business as usual scenarios assumed that 100% of impervious areas would be directly connected to the stormwater drainage infrastructure. This includes buildings, roads, sidewalks, plazas, the sports field and buildings. This model parameter has a strong impact on impervious runoff, and it should be noted that a small change in this assumption could result in significant difference in the results.

Both Option 1 and 2 for business as usual would result in a significant increase in impervious runoff as compared to the baseline conditions (see Table 1, and Figure 1 and Figure 2). As expected, given similar surface cover conditions (see Appendix 2), the two options would create a similar change in runoff, with Option 2 resulting in slightly higher impervious runoff than Option 1. The reduction of pervious runoff is mostly explained by the reduction of pervious areas in Options 1 and 2 as compared to current conditions.

Table 1. Changes in annual surface runoff for Option 1 and 2 (business as usual) as compared to current conditions

Annual runoff (2014)	Baseline conditions	Option 1 (BAU)	Option 2 (BAU)
Impervious runoff (m³)	32,801	61,027	61,516
<i>% change from baseline</i>	-	↑ 86%	↑ 88%
Pervious runoff (m³)	51,834	25,799	25,125
<i>% change from baseline</i>	-	↓ 50%	↓ 52%




Figure 1. Impervious runoff in current conditions and future development Options 1 and 2 (business as usual)




Figure 2. Pervious runoff in current conditions and future development Options 1 and 2 (business as usual)

Green infrastructure in Option 1:

The Option 1 business as usual scenario was used to test the effectiveness of green infrastructure for reducing stormwater runoff. The green infrastructure tested included rain gardens, cisterns and green roofs. They were tested individually to estimate how much of each infrastructure type would be required to achieve a net zero target. The net zero target assumes, as compared to current conditions:

- No increase in monthly and annual surface runoff (both pervious and impervious) for 2014 weather
- No increase in impervious runoff peak flow for the 2-year storm event

Rain gardens:

The model indicates that UBC could achieve a net zero increase in surface runoff in Stadium Road neighbourhood by using existing pervious surface (herbaceous and shrubs) for water retention with the following interventions:

- Draining 47% of the area’s impervious surfaces into its pervious surfaces
- Providing 178 m³ of pervious depression storage in existing pervious areas to manage the runoff, which corresponds to a 6.5 mm depth over all 27,334 m² of pervious areas

This storage would allow for maintaining current annual runoff as well as impervious peak flow for a 2-year rain event. However, it would result in an increase in total pervious runoff and peak flow due to the draining of impervious surfaces onto pervious areas.

Green roofs:

UBC would be 2% shy of achieving their net zero target for impervious runoff by making a 100% of their building rooftops, and underground parking into green roofs. This represents a 31% reduction of impervious surfaces in the neighbourhood and would increase total neighbourhood pervious runoff back to the current conditions level.

However, approximately 25,000 m³ of that pervious runoff would be generated by saturated green roof surfaces. If the green roofs' runoff was to be drained into UBC's stormwater drainage infrastructure, green roofs would not allow for reaching the net zero target; they would reduce runoff by nearly 10% as compared to the business as usual scenario, which would still represent a 78% increase from current conditions.

Cisterns and dry ponds:

Cisterns and dry ponds are both estimated using the impervious depression storage in the i-Tree Hydro. The net zero target could be reached by:

- Draining 44% of impervious areas into cistern or dry pond storage
- Providing 140 m³ of storage in cistern(s) or dry pond(s)

Comparative efficiency of green infrastructure options:

As a measure of the efficiency of each treatment, we calculated the approximate changes in surface runoff from each unit area or volume of interventions as compared to the business as usual scenario for Option 1. We added a natural forest stand contribution per square metre which is based on the contribution of the Ropes course to stormwater management in the neighbourhood. These results were presented in the previous memo. Table 2 summarizes the results from that analysis. The comparison was conducted using surface runoff to account for reductions in impervious flow as well as increases in pervious flow from saturated soils which would be produced by green roofs.

Table 2. Relative impact of green infrastructure options on surface runoff

Impact	Rain gardens	Green roofs	Cisterns	Dry ponds	Natural forest stand
Total green infrastructure area or volume in the neighbourhood	27,334 m ² (depth of 6.5 mm)	25,886 m ²	140 m ³	140 m ³	15,286 m ²
Total change of surface runoff (m ³)	-4,482	-2,793	-1,803	-1,803	-2,223
Change of surface runoff (m³) per square or cubic metre of green infrastructure	-1.26 m³	-0.11 m³	-12.85 m³	-12.85 m³	-1.06 m³ (*)
Change in water quality (pollutant load)	-3%	-3%	-2%	-2%	-3%

*Note: the natural forest stand change in runoff only accounts for the change in impervious runoff, as it is assumed that pervious runoff for the forest stand drains into other pervious areas outside of the project boundary such as the Botanical garden. This is in contrast with pervious runoff generated from green roofs, which would require to be drained from the roofs.

Overall, cisterns and dry ponds provide the most efficient reduction in surface runoff, followed by rain gardens. Green roofs are less effective at reducing surface runoff due to the generation of runoff from the saturated soils.


Cisterns and a combination of open drainage ditches that could be engineered to overflow into surrounding depressed, permeable surfaces would be ideal to help meet both the stormwater goals and biodiversity objectives.

This memo will be followed-up by a final analysis of a mixed green infrastructure scenario for Option 1 which will integrate policy options of interest to UBC Campus + Community Planning. This scenario will be designed to achieve a net zero target and will also be tested to a climate change 2-year rain event in order to test for the possibility to achieve net zero given the expected changes in weather patterns.

Please do not hesitate to call us if you have any questions regarding the material discussed in this report.

Sincerely,

Project Staff:



Camille Lefrançois
B.A.&Sc., M.Sc. (Planning)
MCIP Candidate

Contact Information:

Phone: 604-733-4886
Email: camille@diamondheadconsulting.com or trevor@diamondheadconsulting.com
Website: www.diamondheadconsulting.com

Insurance Information:

WCB: # 657906 AQ (003)
General Liability: Northbridge General Insurance Corporation - Policy #CBC1935506, \$10,000,000
Errors and Omissions: Lloyds Underwriters – Policy #1010615D, \$1,000,000

Limiting Conditions:

- 1) Unless expressly set out in this report or these Assumptions and Limiting Conditions, Diamond Head Consulting Ltd. (“Diamond Head”) makes no guarantee, representation or warranty (express or implied) regarding this report, its findings, conclusions or recommendations contained herein, or the work referred to herein.
- 2) The work undertaken in connection with this report and preparation of this report have been conducted by Diamond Head for the “Client” as stated in the report above. It is intended for the sole and exclusive use by the Client for the purpose(s) set out in this report. Any use of, reliance on or decisions made based on this report by any person other than the Client, or by the Client for any purpose other than the purpose(s) set out in this report, is the sole responsibility of, and at the sole risk of, such other person or the Client, as the case may be. Diamond Head accepts no liability or responsibility whatsoever for any losses, expenses, damages, fines, penalties or other harm (including without limitation financial or consequential effects on transactions or property values, and economic loss) that may be suffered or incurred by any person as a result of the use of or reliance on this report or the work referred to herein. The copying, distribution or publication of this report (except for the internal use of the Client) without the express written permission of Diamond Head (which consent may be withheld in Diamond Head’s sole discretion) is prohibited. Diamond Head retains ownership of this report and all documents related thereto both generally and as instruments of professional service.
- 3) The findings, conclusions and recommendations made in this report reflect Diamond Head’s best professional judgment given the information available at the time of preparation. This report has been prepared in a manner consistent with the level of care and skill normally exercised by arborists currently practicing under similar conditions in a similar geographic area and for specific application to the trees subject to this report on the date of this report. Except as expressly stated in this report, the findings, conclusions and recommendations it sets out are valid for the day on which the assessment leading to such findings, conclusions and recommendations was conducted. If generally accepted assessment techniques or prevailing professional standards and best practices change at a future date, modifications to the findings, conclusions, and recommendations in this report may be necessary. Diamond Head expressly excludes any duty to provide any such modification if generally accepted assessment techniques and prevailing professional standards and best practices change.
- 4) Nothing in this report is intended to constitute or provide a legal opinion and Diamond Head expressly disclaims any responsibility for matters legal in nature (including, without limitation, matters relating to title and ownership of real or personal property and matters relating to cultural and heritage values). Diamond Head makes no guarantee, representation or warranty (express or implied) as to the requirements of or compliance with applicable laws, rules, regulations, or policies established by federal, provincial, local government or First Nations bodies (collectively, “Government Bodies”) or as to the availability of licenses, permits or authorizations of any Government Body. Revisions to any regulatory standards (including by-laws, policies, guidelines and any similar directions of a Government Bodies in effect from time to time) referred to in this report may be expected over time. As a result, modifications to the findings, conclusions and


recommendations in this report may be necessary. Diamond Head expressly excludes any duty to provide any such modification if any such regulatory standard is revised.

- 5) Diamond Head shall not be required to give testimony or to attend court by reason of this report unless subsequent contractual arrangements are made, including payment of an additional fee for such services as described in the fee schedule and contract of engagement.
- 6) In preparing this report, Diamond Head has relied in good faith on information provided by certain persons, Government Bodies, government registries and agents and representatives of each of the foregoing, and Diamond Head assumes that such information is true, correct and accurate in all material respects. Diamond Head accepts no responsibility for any deficiency, misinterpretations or fraudulent acts of or information provided by such persons, bodies, registries, agents and representatives.
- 7) Sketches, diagrams, graphs, and photographs in this report, being intended as visual aids, are not necessarily to scale and should not be construed as engineering or architectural reports or surveys.
- 8) Loss or alteration of any part of this report invalidates the entire report.

Appendix 1 Maps of Site Conditions

The maps below depict the current Stadium Road neighbourhood conditions, followed by maps of the future development business as usual for Options 1 and 2.

Current Neighbourhood Condition



Stadium Road Neighbourhood
i-Tree Hydro Assessment


Surface

- Canopy
- Canopy
- Herbaceous (lawn)
- Impervious - Directly Connected
- Impervious - Disconnected
- Shrubs
- Bare soil

Map prepared: August 10, 2018



SRN Development Option 1



**Stadium Road Neighbourhood
i-Tree Hydro Assessment**

- SRN Project Boundary
- Underground Parking Boundary

Scenario 1: Business as usual

Impervious cover (66%)

- Buildings
- Road
- Pavement
- Field
- Plaza 1, 75% imperv
- Plaza 2, 25% imperv


Pervious cover (20%)

- Grass
- Bare soil


Canopy (14%)

- Canopy (evergreen)
- Canopy (deciduous)

Map prepared: September 24, 2018



SRN Development Option 2



**Stadium Road Neighbourhood
i-Tree Hydro Assessment**

-  SRN Project Boundary
-  Underground Parking Boundary

Scenario 2: Business as usual

Impervious cover (66%)

-  Buildings
-  Road
-  Pavement
-  Field

Pervious cover (16%)

-  Grass
-  Bare soil

Canopy (18%)

-  Canopy (evergreen)
-  Canopy (deciduous)

Map prepared: September 24, 2018



Appendix 2 Surface Conditions

1.1 Current baseline conditions

Current Conditions			
Surface Cover Type	Percent	Sub-category	Percent
Tree canopy	22.59%	Over pervious soil	21.29%
		Over impervious surfaces	1.30%
		<i>total</i>	22.59%
		Evergreen tree	18%
Shrubs	2.65%	Evergreen shrub	50%
Herbaceous (lawn)	28.00%		
Water	0.00%		
Impervious	46.67%	Directly connected impervious areas	76%
Bare soil	0.08%		
TOTAL	100%		

1.2 Future development scenarios

Option 1 (Business as usual)				Option 2 (Business as usual)			
Surface Cover Type	Percent	Sub-category	Percent	Surface Cover Type	Percent	Sub-category	Percent
Tree canopy	13.94%	Over pervious soil	12.23%	Tree canopy	18.01%	Over pervious soil	15.02%
		Over impervious surfaces	1.71%			Over impervious surfaces	2.99%
		<i>total</i>	13.94%			<i>total</i>	18.01%
		Evergreen tree	9.05%			Evergreen tree	13.24%
Shrubs	1.84%	Evergreen shrub	50%	Shrubs	1.59%	Evergreen shrub	50%
Herbaceous (lawn)	16.59%			Herbaceous (lawn)	14.33%		
Water	0.00%			Water	0.00%		
Impervious	66.10%	Directly connected impervious areas	100%	Impervious	65.48%	Directly connected impervious areas	100%
Bare soil	1.52%			Bare soil	0.59%		
TOTAL	100%			TOTAL	100%		

Appendix 3 Baseline & Business as Usual Scenarios Model Assumptions

Hydrological Parameter	Input value
Soil type	Sandy loam
Upper soil conditions	
Depth of soil under soil zone (m)	1
Initial soil saturation (%)	85
Advanced settings	
Leaf transition period	28
Leaf on day (Day of year)	122
Leaf off day (Day of year)	285
Tree bark area index	1.7
Shrub bark area index	0.5
Leaf storage (mm)	0.2
Pervious depression storage (mm)	1.0
Impervious depression storage (mm)	2.5
Scale Parameter of Soil Transmissivity	0.023
Transmissivity at Saturation (m ₂ /h)	0.13
Unsaturated Zone Time Delay (h)	10
Time Constants for Surface Flows: Alpha (h)	40.0
Time Constants for Surface Flows: Beta (h)	40.0
Time Constant for Subsurface Flow: B (h)	120.0
Soil Macropore Percentage	0.000001
Watershed area where rainfall rate can exceed infiltration rate (%)	100